

Job Name/Location:

Tag No.:

Date:

For:	File	Resubmit
	Approval	Other_____

PO No.:

Architect:

GC:

Engr:

Mech:

Rep:

(Company)

(Project Manager)



# PRARH1

Auxiliary Heater Relay Kit for Multi V, Single-Zone, and Multi F IDUs

**Electrical:**

Power Supply	12VDC (From Indoor Unit)
--------------	--------------------------

**Operation Conditions:**

Operating Temperature	14 to 158°F
Storage Temperature	-4 to +176°F
Humidity	0 – 98% Non-Condensing

**Unit Data:**

Dimensions (W x H x D, in.)	7-9/32 x 3-13/32 x 2-9/32
Contact Rating	3A @ 24VAC

**Connectivity:**

LG Communications Cable	V-Net 30" Wiring Harness (included)
-------------------------	--

**Standard Features:**

- Provides ability to use the two stage auxiliary heater as the primary or secondary heating source
- Compatible LG indoor units: High Static Ducted, Low Static Ducted, Mid Static Ducted, Multi-Position Air Handling, 1Way Ceiling Cassette, 2Way Ceiling Cassette, 4Way Ceiling Cassette, and Ceiling Suspended

**Notes:**

1. If a Third-Party Dry Contact and an LG internal heater or an LG Auxiliary Heater Kit is installed, supplemental heat capability cannot be controlled by the Third-Party Thermostat.
2. Must follow installation instructions in the applicable LG installation manual.

