(c)/(p)09106LGE
This drawing is the property of LGE and it is protected by the concerned laws and regulation.

CTQ Table

No.	CTQ Item	Unit	Value & Tolerance			Z-Value	
			Target	LSL	USL	Zst	Zlt
1							
2							
3							
4							

Dimension

검도부 치수 (CTQ)*(Y Dimension)	제품 성능 및 안전성 등의 중요 품질에 영향을 주는 핵심 특성치(Core characteristic value which can make a serious effect to function or safety of the product)	
양산부 치수 (Mass production management dimension)	양산 제품의 동일성 확보 목적을 위한 치수로, 입고 검사 항목에서 품질관리 시 관리대상이 됨 ※Dimension for the specification deviation management of the mass production part, it should be checked with incoming inspection by QA/QC or outgoing inspection by supplier.	
개발부 치수 (Development management dimension)	금형의 올바른 제작과 제품을 위한 치수로, 제작 공정능력 향상 위한 모델링 작업 ※Dimension for new equipment's approval, all that dimension should be checked at PR-stage for approval.	
참고치수 (Reference Dimension)	설계 사양 변경 등 공정능력 확인을 위한 치수로 실제 품질관리 항목 아님 ※Dimension for the design concept application or Welding marking, or another reference.	

Mark

Mark	Drawing Yes/No	To be?
	Y	X
	Y	X
	-	X
	-	X

General Tolerance

Length(mm)

Mark	Classification(+/-LS)	0.5~3	3~6	6~30	30~120	120~400	400~1000	1000~2000	2000~4000
F	Fine (+/-Grade)	0.05	0.05	0.1	0.15	0.2	0.3	0.5	-
M	Medium (+/-Grade)	0.1	0.1	0.2	0.3	0.5	0.8	1.2	2.0
C	Coarse (+/-Grade)	0.2	0.3	0.5	0.8	1.2	2.0	3.0	4.0
V	Very Coarse (+/-Grade)	-	0.5	1.0	1.5	2.5	4.0	6.0	8.0

Toierance

Tolerance Grade		Round/Chamfer(±mm)			Angle (±Degree' Minute" Second")			
Mark	Classification(+/-LS)	0.5~3	3~6	6<L≤	L≤10	10<50	50<120	120<400	400<L
F	Fine (+/-Grade)	0.2	0.5	1.0	1°	30'	20'	10'	5'
M	Medium (+/-Grade)	0.2	0.5	1.0	1°	30'	20'	10'	5'
C	Coarse (+/-Grade)	0.4	1.0	2.0	1°30'	1°	30'	15'	10'
V	Very Coarse (+/-Grade)	0.4	1.0	2.0	2°	1°	1°	30'	20'



3D VIEW





OP1	OP2	OP3	OP4	OPT. CUTTING
ZPALD37SRA	ZPALD37SRA	ZPALD37SRA	ZPALD37SRA	
Qty	Qty	Qty	Qty	NO
-	-	-	1	1
1	1	-	-	1
-	-	1	-	1
1	1	-	-	2
-	-	-	1	2
-	-	1	-	2
-	-	-	1	3
-	-	1	-	3
-	-	-	1	4
-	-	-	1	4
-	-	-	1	4
-	-	-	1	4
1	1	1	1	5
1	1	1	1	6

P.NO	DESCRIPTION	SPEC
AJF73087801	Structure Assembly,Module(Indoor)	ASC#2518AG EAU63823301 AHU75133301 ZPALD37SRA_AMBULUS TR 2024 NEW
AJF73087801	Structure Assembly,Module(Indoor)	ASC#2518AG EAU63823301 AHU75133301 ZPALD37SRA_AMBULUS TR 2024 NEW
ACT30004401	Cycle Assembly,Module(Indoor)	4DL05918202 ZPALD37SRA TR Multi V R32 1Φ 60Hz For USA
ACT30004401	Cycle Assembly,Module(Indoor)	4DL05918203 ZPALD37SRA TR Multi V R32 1Φ 60Hz For USA
ABQD29150201	Case Assembly,Control Module(Indoor)	ZPALD37SRA TR 2024 NEW
ABQD29150301	Case Assembly,Control Module(Indoor)	ZPALD37SRA TR 2024 NEW
ABQD29150401	Case Assembly,Control Module(Indoor)	ZPALD37SRA TR 2024 NEW
ABQD29150501	Case Assembly,Control Module(Indoor)	ZPALD37SRA TR 2024 NEW
AMA34178501	Accessory Assembly,Module(Indoor)	ZPALD37SRA TR Multi V R32 For USA
AMA34178504	Accessory Assembly,Module(Indoor)	ZPALD37SRA TR Multi V R32 For USA
AMA34178505	Accessory Assembly,Module(Indoor)	ZPALD37SRA TR Multi V R32 For USA
AMA34178506	Accessory Assembly,Module(Indoor)	ZPALD37SRA TR Multi V R32 For USA
AMK30002401	InterFace Assembly,Module	ZPALD37SRA TR Multi V R32 For USA
ADF30731201	Package Assembly,Indoor	TR TTF GLOBAL 12 NEW (UPC#010,LGE,LAP)

재질/SPEC/MATERIAL)
1. 각 재질 및 부품 Spec.은 신품 도면을 참조할 것.
2. 본 부품은 LG전자의 Level A-1 유해물질 관리기준을 참조하고 준수해야 함. 상세 내용은 LGETH 유해물질 관리규정 LG1101-A-9025 및 협력사 제품 유해물질 관리 운용 가이드를 참조할 것.
HBCDD, TCEP, TCCPP 등의 사용이 Level A-II 등급은 사용해선 유해물질 관리 기준을 참조할 것.

3. 기타 재료의 상세품은 협력업 Maker의 승인하에 준할 것.
생산기술/PRODUCTION)
1. 신규 사상 시에 협력업 및 도장사 검토를 위한 자료는 3D Data 참조할 것.
2. 찍힘, 찌그러 짝힘, 변형, 흠이 발생되지 않도록하며, 내부에 이물질이 들어가 있으면 안 됨.

3. 제조시 외관상 흠이나 이물질 검출이 발생하지 않도록 할 것.
4. 그림 없는 일반 공차는 IM3003 제조사를 따를 것.
품질보증/INSPECTION)
1. "◇" 표시 부위는 개발 관리 치수로 관리할 것.
" ◇ " 표시 부위는 양산 관리 치수로 관리할 것.

신뢰성기준/RELIABILITY)
해당없음.

MATERIAL SPECIFICATIONS
1. Refer to the single item drawing for each material and part spec.
2.This part should comply with the criteria of Level A-I restricted hazardous substances which refers to LGE standard LG1101-A-9025 and the hazardous substance management manual for the supplier. Level A-II restricted substances such as HBCDD, TCEP, TCCPP should comply with hazardous substances inspection standard by each division.
3. Details of other materials should be in accordance with the approval of raw material maker.
PRODUCTION SPECIFICATIONS
1. Refer to 3D Data for dimension for assembly review, excluding drawing dimensions.
2. When transporting, do not get any marks, deformations or scratches, and do not allow foreign matter to penetrate inside.
3. The surface should be no harmful defects or scratching in operation.
4. The assembly method and procedure should follow the WISEL(Work Instruction Support System)
INSPECTION SPECIFICATIONS
1. "◇" marked dimensions are developent management dimension and should be controlled.
" ◇ " marked dimensions are mass production management dimension and should be controlled.
RELIABILITY SPECIFICATIONS
N/A

SYM	REVISION	ECO NO.	DATE	PREPARED
A5				
A4				
A3				
A2				
A1				

DIE/MOLD TYPE		UNIT	mm	SCALE	1/4
동사출부 (Injection Mold)		DESIGNED	REVIEWED	CHECKED	APPROVED
DIE MAKER	MANUFACTURER	작성일자	검토일자	승인일자	승인일자
동사업부 (Customer Injury)	동사업부 (Customer Injury)	작성자	검토자	승인자	승인자

LG Electronics

TITLE: Unit Assembly,Indoor
TR Chassis
DWG NO.: AJT3016051(1/2)
SHEET NO.: 1 OF 1

SYM	REVISION	ECO NO.	DATE	PREPARED
A5				
A4				
A3				
A2				
A1				

DIE/MOLD TYPE		UNIT	mm	SCALE	1/4
동사출부 (Injection Mold)		DESIGNED	REVIEWED	CHECKED	APPROVED
DIE MAKER	MANUFACTURER	작성일자	검토일자	승인일자	승인일자
동사업부 (Customer Injury)	동사업부 (Customer Injury)	작성자	검토자	승인자	승인자

LG Electronics

TITLE: Unit Assembly,Indoor
TR Chassis
DWG NO.: AJT3016051(2/2)
SHEET NO.: 1 OF 1

No.	Code	Description	Q'ty	Weight(kg)
04	ZPALD37SRA AMBULUS TR Multi V R32 For USA		02	14.2
03	ZPALD37SRA AMBULUS TR Multi V R32 For USA		01	14.2
02	ZPALD37SRA AMBULUS TR Multi V R32 For USA		03.2	15.4
01	ZPALD37SRA AMBULUS TR Multi V R32 For USA		03.2	15.4
BOM	Spec		Net Weight(kg)	Gross Weight(kg)



01,02 작업
EXPLODED VIEW



03,04 작업
EXPLODED VIEW