

Job Name/Location:

Tag #:

Date:

PO No.:

Architect:

Engr:

Rep:

(Company)

For:

☐ File

☐ Resubmit

☐ Approval

☐ Other _____

GC:

Mech:

ZVRCZTRH1

Temperature and Humidity Sensor

for CRC2 Series and MS8000 Series Controllers

Model: ZVRCZTRH1

Function: Temperature, Humidity

Electrical:

Power: 3.6V lithium battery (10yr. non-replaceable)



Wall Mounted Temperature & Humidity Sensor

Connectivity:

Wireless Communications

2.4GHz mesh network

ZigBee® HA3.0 Compatible

Range up to 40ft; 300 ft open field

Type of Measurement:

Temperature:

Range: 32 to 122°F (accuracy: +/- 0.5 °F)

Humidity:

Range: 0 to 100 % (accuracy: +/- 3 %)

MultiSITE CRC2 Remote Controller Additional Accessories (sold separately):

☐ ZVRCZPWC2 - ZigBee® Pro Wireless Module^{2,3}

☐ ZVRCZDWC1 Wireless Door Window Contact²

☐ ZVRCZMTH1 - Wireless Ceiling Mounted Occupancy,

☐ Temperature and Humidity Sensor²

☐ ZVRCZWOC1 - Wireless Wall Mounted Occupancy Sensor²

☐ SEDCO2G5045 - Wireless CO2, Temperature, & Humidity Sensor²

☐ ZVRCZTRH1 - Wireless Temperature & Humidity Sensor²

☐ ZVRCZWLS1 - Wireless Water Leak Sensor² VCM8002V504 -

☐ Wi-fi Card Module (BACnet wireless IP)

Notes:

1. Available functions/features may differ based on connected system.

2. Up to 20 Zigbee sensors can be connected to a MultiSITE CRC2 Series Remote Controller & MS8000 Series Room Controller

3. The ZVRCZPWC2 is for use with the CRC2 and not for use with the CRC1 or MS8000 Series Room Controllers.

Job Name/Location:

ZVRCZTRH1

Temperature and Humidity Sensor

for CRC2 Series and MS8000 Series Controllers



Tag #:

Date:

PO No.:

ZVRCZTRH1 Wall Mounted Temperature, and Humidity Sensor

Dimensions: 2.85" L x 3.25" W x 0.71" H

Battery Voltage: 3.6VDC Lithium

Ambient Temperature: 32°F to 122°F (0°C to 50°C)

