

Job Name/Location:

Tag No.:

Date:

For:	File	Resubmit
	Approval	Other_____

PO No.:

Architect: GC:

Engr: Mech:

Rep: (Company) (Project Manager)

KSSSA481A120-D1

R32 Single-Zone System with LGRED® - A-Coil + Gas Furnace (96%)

A-Coil Unit - LKMMMA48D1, Outdoor Unit (ODU) - KUSXA482A, Gas Furnace - LNAVE120D1

**Performance:****Cooling:**

Cooling Capacity (Min~Rated~Max) (Btu/h)	18,200~48,000~51,000
SEER2	17.3
EER2	11.00

SEER - Seasonal Energy Efficiency Ratio

EER - Energy Efficiency Ratio

Heating:

Heating Capacity (Min~Rated~Max) (Btu/h)	19,500~50,000~55,000
HSPF2	9.5
Max. Heating @ Indoor 70°F DB	46,400
Outdoor 17°F WB	43,000
Outdoor 5°F WB	37,000
Outdoor -4°F WB	37,000

HSPF - Heating Seasonal Performance Factor

Outdoor Unit Electrical:

Power Supply (V/Hz/Ø)	208-230/60/1
MOP (A)	40
MCA (A)	32
Cooling Rated Amps (A)	17.1
Heating Rated Amps (A)	18.5
Compressor (A)	22.0
Fan Motor (ODU) (A)	1.6 + 1.6
Cooling Power Input (Min~Rated~Max @95°F) (kW)	1.53~4.364~4.75
Heating Power Input (Min~Rated~Max @47°F) (kW)	1.33~3.800~4.75

MOP - Maximum Overcurrent Protection

MCA - Minimum Circuit Ampacity

Outdoor Unit Piping:

Liquid (in., O.D.) ²	3/8 Flare
Vapor (in., O.D.) ²	5/8 Flare
Additional Refrigerant (oz./ft.)	0.43
Min. / Max. Pipe Length (ft.) ³	16.4 / 246
Piping Length (no add'l refrigerant, ft.)	24.6
Max. Elevation (ft.)	98.4

Outdoor Unit Operating Range:

Cooling (°F DB)	5 ~ 118
Heating (°F WB)	-13 ~ +64

Outdoor Unit Features:

- Inverter (Variable Speed) Compressor
- Built-in Communication Kit

A-Coil Features:

- Aluminum Coil
- Fully Insulated Cabinet
- High Efficiency "A" Coil
- Built-in plenum flanges for fast and safe installation
- Multi-Position Installation: Vertical, Downflow, or Horizontal
- Vertical and Horizontal Drain Pans
- Left and Right Drain Connections
- Factory installed TXV's with bolt on connections
- Factory installed Refrigerant Detection sensor

Gas Furnace Features:

- Aluminized steel tubular heat exchanger
- Hot-surface ignition
- Multi-speed direct-drive blower
- Designed for multi-position installation

Optional Accessories:

- ☐ LG Airzone Aidoo Pro Wi-Fi Controller - AZAI6WSPLGE
- ☐ Drain Pan Heater - PQSH1200
- ☐ Single-Port Shutoff Valve - PRHPZ010A
- ☐ Low Ambient Wind Baffle (Cooling operation to -4°F) - ZLABGP04B Requires 2

Outdoor Unit Data:

Compressor Type x Qty.	R1 Scroll
Refrigerant Type	R32
Refrigerant Control	EEV - ODU, TXV - A-Coil
Pre-Charge + Additional Charge for A-Coil (lbs.)	7.50 + 0.88
Sound Pressure (Cooling / Heating) (±1 dB[A]) ⁴	54 / 56
Net / Shipping Weight (lbs.)	213.4 / 232.4

Fan:

ODU Fan Type x Qty.	Axial x 2
ODU Fan Speeds (Fan/Cool/Heat)	4 / 5 / 5
ODU Motor/Drive	Brushless Digitally Controlled/Direct
ODU Air Flow Rate (CFM)	1,942 x 2
Air Flow Range through A-Coil (CFM) (Min. ~ Max.)	1,200~1,600
Corresponding ESP Range (in. w.g.) (Min. ~ Max.)	0.1~0.8
Dehumidification (pts./hr.)	8.06

A-Coil Unit Data:

Nominal Capacity (Btu/h)	48,000
Type	24.5 inch
Coil Material	Aluminum
Case Width x Height x Depth (in.)	24-1/2 x 34 x 21
Net / Shipping Weight (lbs.)	73 / 82
Liquid Piping (in., O.D.) ²	3/8 Braze
Vapor Piping (in., O.D.) ²	3/4 Braze

Gas Furnace:

Performance:	
Input (Btu/h) (Natural/Propane)	120,000/120,000
Output (Btu/h) (Natural/Propane)	115,000/115,000
Air Temperature Rise (°F)	40-70
Design Max. Outlet Air Temp. (°F)	170
AFUE	96

Gas Furnace Data:

Blower Type / Fan Speed No.	Sirocco/5
Motor Type	ECM
Airflow Range (CFM)	1,165~1,998
Ignition Type / No. of Burners	Automatic/6
Min./Max. Inlet Gas Pressure (Natural, in. w.c.)	4.5/10.5
Min./Max. Inlet Gas Pressure (Propane, in. w.c.)	11/13
Case Width x Height x Depth (in.)	24-1/2 x 33-3/4 x 28-1/2
Shipping Weight (lbs.)	210

Gas Furnace Electrical:

Power Supply (V/Hz/Ø)	115/60/1
MOP (A)	20
MCA (A)	14

AFUE - Annual Fuel Utilization Efficiency

Must follow installation instructions in the applicable LG installation manual.

LGRED®

For a complete list of available accessories, contact your LG representative.

For continual product development, LG reserves the right to change specifications without notice.

© LG Electronics U.S.A., Inc., Englewood Cliffs, NJ. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. /www.lghvac.com

SB_SZ_LGRED_A-Coil_Furnace_ODU_R32_KSSSA481A120-D1_02_26

Page 1 of 4

KSSSA481A120-D1
R32 Single-Zone System with LGRED° - A-Coil + Gas Furnace (96%)
A-Coil Unit - LKMMMA48D1, Outdoor Unit (ODU) - KUSXA482A, Gas Furnace - LNAVE120D1






Tag No.: _____
Date: _____
PO No.: _____

- Notes:**
- 1. Acceptable operating voltage: 187V-253V.
 - 2. Adapters for piping connections are shipped with the outdoor unit.
 - 3. Piping lengths are equivalent.
 - 4. Sound Pressure levels are tested in an anechoic chamber under ISO Standard 3745.
 - 5. All power supply wiring to the outdoor unit is field supplied, solid or stranded. The power wiring and the communication wiring from the outdoor unit to the third-party, field-supplied furnace is field supplied and must be stranded, shielded or unshielded (if shielded, it must be grounded to the chassis of the outdoor unit only). All wiring must comply with applicable local and national codes.

- a. Power Supply Wiring to Outdoor Unit (No. x AWG): 3 x 12 for 18k and 24k; 3 x 10 for 30k, 36k, 42k, and 48k.
- b. Power Supply Wiring to the third-party Furnace is to be specified by the manufacturer.
- c. Control Cable between the Outdoor Unit and the third-party Furnace (No. x AWG): 6 x 18.
- d. The 24V Control Power to the A-Coil is to be sourced from the third-party Furnace.
- e. The Control Cable between the third-party Furnace and the thermostat (No. x AWG): 6 x 18.
- 6. Nominal data is rated 0 ft. above sea level, with 25 ft. of refrigerant line and a 0 ft. level difference between outdoor and indoor units.
- 7. Must follow installation instructions in the applicable LG installation manual.

LKMMMA48D1, LKMMMA60D1




UNLESS OTHERWISE SPECIFIED:
ALL BENDS 90 DEGREES.
ANGLES +/- 2 DEGREES.
ALL HOLE SIZES +/- .010
ALL HOLE TO HOLE DIM. +/- .015
X.X +/- .125
X.XX +/- .063
X.XXX +/- .032
THICKNESS

KSSSA481A120-D1
R32 Single-Zone System with LGRED° - A-Coil + Gas Furnace (96%)
A-Coil Unit - LKMMMA48D1, Outdoor Unit (ODU) - KUSXA482A, Gas Furnace - LNAVE120D1



Tag No.: _____
Date: _____
PO No.: _____

Unit: Inches (mm)



Furnace Size	A Cabinet Width (in. [mm])	D Supply Air Width (in. [mm])	E Return Air Width (in. [mm])
LNAVE060B1	17.5 (445)	16 (406)	15-27/32 (402)
LNAVE080B1	17.5 (445)	16 (406)	15-27/32 (402)
LNAVE080C1	21 (533)	19.5 (495)	19-13/32 (493)
LNAVE100C1	21 (533)	19.5 (495)	19-13/32 (493)
LNAVE120D1	24.5 (622)	23 (584)	22-27/32 (580)

KSSSA481A120-D1

R32 Single-Zone System with LGRED° - A-Coil + Gas Furnace (96%)

A-Coil Unit - LKMMMA48D1, Outdoor Unit (ODU) - KUSXA482A, Gas Furnace - LNAVE120D1



Tag No.: _____

Date: _____

PO No.: _____

